

Model: SF-BF-SB01



Product Features

- ◆ Easy to install and use
- ◆ Clear and smooth video browsing; intelligent transmission giving full play to capabilities of the network
- ◆ Online firmware upgrade, and synchronous updating of the functions and experience
- ◆ Two-way voice intercom supported; echo eliminated; noise suppressed
- ◆ Compatible with Android; remote real-time monitoring supported with the IOS intelligent terminal
- ◆ 2-megapixel high resolution (1920X1080) for clear picture quality
- ◆ Lighting for infrared night vision (with a night vision distance of 7m); 24h around-the-clock monitoring; IR-CUT switching; free of color cast in the daytime; clearer night vision
- ◆ The built-in rechargeable lithium battery with long battery life functions for up to 6 months under normal circumstances and can stand by for 12 months
- ◆ 2.4G Wi-Fi supported (IEEE802.11b/g/n)
- ◆ Cloud storage, Micro SD card (up to 128GB) and mobile phone video recording supported
- ◆ QR code intelligent connection and network allocation supported
- ◆ Supporting human contour detection, activity zone, intelligent push and pet snapshot, Package inspection (value added service required)
- ◆ IP65 Easy installation: support 1 / 4 universal screw bracket

Specifications

Master Processor	SOC	T31ZL
Image Sensor	Sensor	1/2.9" color CMOS Sensor
	Lens	F2.0, 2-megapixel
	Visual angle	Diagonal 140° Horizontal 117° Vertical 61°
	Minimum Illumination	0.01 Lux
Audio	Input/Output	Two-way voice intercom available (built-in Microphone and speaker)
	Audio Compressing Method	AAC
Video	Video Compressing Method	H.264/H.265
	Lighting Frequency	50Hz, 60Hz
	Image Frame Rate	15 fps
	Maximum Image Resolution	1920*1080P
	Light Source for Night Vision	Optional infrared and white lights
Network	Wireless Network	2.4G Wi-Fi (IEEE802.11b/g/n), External antenna
	Protocols Supported	TCP/IP, UDP/IP, DHCP, RTMP, MUDP
	IP Address Supported	Dynamic IP address supported
AI	Intelligent Features	Human contour detection, activity zone, intelligent push, pet snapshot, Package inspection
Alarm Notification	Alarm Methods	Alarm push by mobile APP and alarm sound

Wake-up	Wake-up Method	PIR body induction wake-up, and remote positive wake-up
Video Recording	Recording Method	Alarm triggered recording, and manual recording
	Video Storage	Cloud storage, local Micro SD card, and mobile phone memory
Indicator Lamps	LED Indicator	RGB tri-color lamp indicating the status of power/network signal/functionality
Battery	Capacity	5000mAh
	Removability	Unremovable
	Battery Life	6 months (provided that 20 10s videos are recorded per day)
	Standby Time	1 year
	Charging Voltage	DV 5V±5%/1.5A
	Charge Time	Within 10 hours
	Protection Method	IP65 is dustproof and waterproof; over-current/over-discharge/over-charge/short circuit/charging protection at high & low temperatures
Power Consumption	Standby Power Consumption	1.68mW (4V 0.42mA)
	Power Consumption of Daytime Operation	0.88W (4V 220mA)
	Power Consumption of Operation at Night	2.20W (4V 550mA)
Interfaces	Power Supply	1 Micro USB interface
	SD Card	1 Micro SD card (up to 128GB supported)
	Keys	1 reboot key and 1 on/off key
Installation Method	Installation Method	Bottom 1/4 universal screw hole

Environment	Dustproof and waterproof	IP65
	Operating Environment	-10° ~ 45° C /10% ~ 80% (no condensation)
	Storage Environment	-20° C ~ 60° /0% ~ 90% (no condensation)
Specifications	Size (LxWxH)	IPC size: 67 mm × 58 mm × 89 mm (excluding bracket) Bird feeder size: 378mm × 268mm × 204mm (excluding bracket)
	Material + Process	ABS+PC
	Color	White
Certifications	Certificate	CE, FCC, RoHS, WEEE, MSDS, UN38.3, UL62368, BattG

