

AUDIO CABLE

14 AWG 2 CONDUCTOR

STRANDED CABLE



209-2320 SERIES

Part Number:	Description:
209-2320	Audio Cable, Stranded, Unshielded, 14 AWG 2 C, White 500 ft.
209-2320/BK	Audio Cable, Stranded, Unshielded, 14 AWG 2 C, Black 500 ft.
209-2320/PR	Audio Cable, Stranded, Unshielded, 14 AWG 2 C, Purple 500 ft.

DESCRIPTION

14 AWG 2 Conductor Stranded Bare Copper, Unshielded with an overall jacket.

CONSTRUCTION

Conductor count: 2
Shape: Round
Rip cord: Yes

CONDUCTORS

Material: Stranded bare copper
Trade size: 14 AWG
Stranding: 41/0.25 mm
Insulation material: Polyvinyl Chloride (PVC)
Insulation O.D.: 0.08 in. (2.10 mm)
Insulation color: Red, Black, White, Green

JACKET

Material: Polyvinyl Chloride (PVC)
Thickness: 0.02 in. (0.60 mm)
O.D.: 0.25 in. (6.40 mm)
Marking: VERTICAL 5024318 c(ETL)usAUDIO CABLE 14AWG 2 COND 41 STRANDED OXYGEN FREE CMR FT4 CL3R RoHS XXXFT 53203M0725102

MECHANICAL

Temperature rating: 75° C
Before Tensile Strength (Mpa): ≥13.8
Aging Elongation (%): ≥100
Aging Condition (°Cxhrs): 100x168
After Tensile Strength (Mpa): ≥85% of unaged
Aging Elongation (%): ≥50% of unaged
Cold Bend (-20±2° Cx4hrs): No Crack

SAFETY


NFPA 70 (NEC®) rating: CMR/CL3
Voltage rating: 300 V RMS

PACKED WEIGHT

209-2320: 22 lb (10 kg)
209-2320/BK: 22 lb (10 kg)
209-2320/PR: 22 lb (10 kg)

APPLICATION

- Sound and Audio
- Intercom Systems
- Indoor Applications



VERTICAL CABLE

951.696.7772 California
800.749.2447 Florida
845.391.8318 New York
713.322.7242 Texas



verticalcable.com

Rev. 4/2024
Subject to change without notice.