

AUSTERE

Audio \ User Guide/Owner's Manual

Model numbers:

Audio Interconnect Cable \ 5S-RCAXx-2.0M

Optical Audio Cable \ 5S-OPTxx-2.0M

Subwoofer Cable \ 5S-SUBxx-5.0M



CAUTION Use the Audio cables indoors and in cool dry locations. DO NOT install cables near any heat-emitting appliances, such as radiators or heat registers. DO NOT install where excessive moisture is present.

Austere's Audio cables contain pure gold contacts to reduce the potential for oxidation buildup in your cables. This preserves the purity of the sound for as long as the cables are used. Audio cables included in the Austere product lineup are; Optical Audio, Subwoofer, and Audio Interconnect.

Product Registration

Prior to using your product, please go to www.austere.com/guarantee to register your product and to access our complete limited lifetime guarantee statement.

INSTALLATION

Installing Audio Interconnect Cables

Prior to installation, make sure all your devices are powered off. The audio interconnect cables have color-coded ends: White and Red.

Follow these steps:

1. Plug one end of the audio cable into the source device, ensuring the colors match the corresponding end of the cable.
2. Install the opposing ends directly into the corresponding audio output of your television or receiver, again matching the colors to the corresponding end of the cable.
3. Austere Audio Cables are equipped with LinkFit Connectors to ensure a secure connection. Push with more force to ensure the connectors are fully linked.

Installing Optical Audio Cables



Prior to installation, be sure all your devices are powered off.

1. Remove the protective cap from each end of your optical cable.
2. Plug one end of the optical cable into the connected device (e.g., soundbar), ensuring the orientation of the cable matches the orientation of the optical connector on your device.
3. Carefully install the opposing end directly into the back of your television or receiver.

Installing Subwoofer Cables

Prior to installation, be sure all your devices are powered off.

1. Plug one end of the audio cable into the source device.
2. Install the opposing ends directly into the corresponding audio output of your receiver.
3. Austere Audio Cables are equipped with LinkFit Connectors to ensure a secure connection. Push with more force to ensure the connectors are fully linked.

Technical Support: Please contact our technical support team with installation questions, troubleshooting needs, or general product questions.

- Phone: 1-855-672-0684
- Email: support@ austere.com

Find all documents for Limited Lifetime Guarantee at [Austere.com](https://www.austere.com).



2023 Austere. All rights reserved. Austere and More Than Expected are trademarks of Austere or its affiliates. All other trademarks are the property of their respective owners.