

## NMO Magnet Mounts

### 3 5/8" NMO Magnet Mounts w/ Rubber Boot

- Brass NMO w/gold contact pin • Soft rubber boot on magnet for scratch protection
- Poly bag w/header card for display - UPC coded
- 17 ft. RG-58A/U tinned copper braid 95%, stranded tinned copper center conductor

BR-1030-UHF Chrome zinc housing - UHF PL-259  
BR-1035-UHF Black zinc housing - UHF PL-259

- 17 ft. RG-58/U bare copper braid 95%, solid insulation, solid copper center conductor

BR-1030-MUHF Chrome zinc housing - Mini-UHF  
BR-1030-BNC Chrome zinc housing - BNC Male  
BR-1030-SMA Chrome zinc housing - SMA Male

BR-1035-MUHF Black zinc housing - Mini-UHF  
BR-1035-BNC Black zinc housing - BNC Male  
BR-1035-SMA Black zinc housing - SMA Male

### 3 5/8" NMO Magnet Mounts w/ Rubber Boot - Double Shield RG-58

- 17 ft. low loss RG-58A/U tinned double shield 95% braid + aluminum foil
- Brass NMO w/gold contact pin • Poly bag w/header card • UPC coded

BR-316R Chrome zinc housing - UHF PL-259  
BR-316R-MUHF Chrome zinc housing - Mini-UHF  
BR-317R Black zinc housing - UHF PL-259  
BR-317R-MUHF Black zinc housing - Mini-UHF

### 3 5/8" NMO Magnet Mounts w/ Rubber Boot - BR-195

- 17 ft. super low loss BR-195 cable (see page 22 for specs)
- Brass NMO w/gold contact pin
- Poly bag w/header card for display - UPC coded

BR-346R Chrome zinc housing - UHF PL-259  
BR-346R-MUHF Chrome zinc housing - Mini-UHF  
BR-347R Black zinc housing - UHF PL-259  
BR-347R-MUHF Black zinc housing - Mini-UHF

### 5" Black NMO & UHF Magnet Mounts - Double Shield RG-58

- 17 ft. low loss RG-58 A/U tinned double shield 95% braid + aluminum foil
- Brass NMO w/ gold contact pin • Poly bag w/header card • UPC coded

BR-322 NMO Black steel housing - PL-259  
BR-322-MUHF NMO Black steel housing / Mini-UHF  
BR-354 UHF Black steel housing - PL-259

# browning®

BR-1030 SERIES  
BR-316R SERIES  
BR-346R SERIES

BR-1035 SERIES  
BR-317R SERIES  
BR-347R SERIES



BR-322  
BR-322-MUHF



BR-354



## NMO Trunk Mounts

- Stainless mount • Brass NMO w/gold contact pin • Poly bag w/header card • UPC coded

- 17' low loss RG-58A/U tinned double shield 95% braid + aluminum foil

BR-311 Fits up to 3/8" surface/ UHF/ PL-259  
BR-311-MUHF Fits up to 3/8" surface/ Mini-UHF

BR-314 Adjustable base - UHF/ PL-259  
Fits up to 3/16" surface

- 17 ft. RG-58A/U tinned copper braid 95% & stranded tinned copper center conductor

BR-1020-UHF Fits up to 3/8" surface - UHF/ PL-259  
BR-1020-MUHF Fits up to 3/8" surface/ Mini-UHF

### Adjustable Trunk Mount

- 17 ft. RG-58A/U tinned copper braid 95% & stranded tinned copper center conductor

- Easy screw off UHF PL-259 for small hole installation

- FME Female attached with easy screw off FME Male to UHF Male PL-259 adaptor

BR-1024-UHFE UHF Male PL-259 connector  
Fits up to 3/8" surface

BR-311 SERIES  
BR-1020 SERIES



BR-314



BR-1024-UHFE