

TECHNICAL DATA SHEET

NATURAL FINISH STONE SEALER





DESCRIPTION

Rockstar NATURAL FINISH STONE SEALER is a premium quality solvent-based penetrating sealer used to protect against staining on a wide variety of natural and man-made stones and tiles. **Developed for Marble, Limestone, Travertine, Terrazzo and Concrete Pavers**.

USES

NATURAL FINISH STONE SEALER is applied as the final sealing coat to help protect against staining due to oil and water-based substances such as cooking oils, red wine, and other everyday stain-inducing materials. The ingress of the staining substance is retarded, making the surface easier to clean.

BENEFITS

- · Excellent oil and water repellency
- · Does not change the surface appearance
- · Does not inhibit the water-vapour permeability
- · Rapid curing
- UV Stable

PROPERTIES

Appearance and colour	Colourless to yellowish clear to hazy liquid
Specific Gravity (Water = 1)	0.81 g/ml
Boiling Point	120 - 200°C
Solubility in Water	Not miscible
Elach Point	30°C

APPLICATION INSTRUCTIONS

- Ensure the surface to be sealed is free of excess grout and grout haze, is dry and free of any oils and other surface contaminants.
- Apply NATURAL FINISH STONE SEALER using a lambswool applicator or low pressure hand sprayer (outdoors only). Ensure the surface is fully saturated without leaving pools of sealer. Apply a second coat as soon as the first coat has dried (1-2 hours).
- 3. The product will cure in 12 hours depending on atmospheric conditions.

COVERAGE

Coverage is dependent on the permeability of the stone or tile and is in the range of 6-15 Mt² per Litre / 50 -150ft² per Quart.

PRECAUTIONS

- 4. Do not allow pools of liquid NATURAL FINISH STONE SEALER to dry on the surface.
- Avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.

CLEANING

Clean all equipment with mineral turpentine.

PACKAGING

NATURAL FINISH STONE SEALER is available in 1, 5 and 20 Litre Containers / 1 Quart / 1.32Gal / 5Gal.

STORAGE

Keep container tightly closed when not in use. Store in a cool, dry place out of reach of children.

SAFETY

Classified as Hazardous according to criteria of Worksafe Australia. For further detailed information refer to Material Safety Data Sheet.

DISCLAIMER: The advice and information contained herein is based on our best knowledge of the product. We believe the information to be accurate and reliable as at the date supplied, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, reliability, or completeness of the advice and information. We urge persons receiving this advice and information to make their own determination as to the advice and information's suitability and completeness for their own particular situation. When in doubt it is always prudent to perform a trial on a scrap section of material, or inconspicuous section of the job to ascertain the products suitability.