



Lighting that connects

DATASHEET

Light Panel for business

The Light Panel for the iContact Camera Pro ensures you always look your best in any environment with adjustable color temperature and brightness controls. Powered by a rechargeable 3100mAh lithium-ion battery, it delivers long-lasting performance for extended sessions without the need for constant charging. Featuring 160 high-quality LEDs rated at 90+ CRI, the panel provides soft, broad-fill light that eliminates harsh shadows and blotchy colors for natural, even illumination. Designed to connect seamlessly to your iContact Camera Pro, it combines professional-grade lighting with a sleek, clutter-free aesthetic.

- **Adjustable Brightness and Color Temperature:** Customize your lighting with color temperatures ranging from 2500K to 6500K and brightness levels up to 1500 lux.
- **Rechargeable Battery:** Powered by a 3100mAh lithium-ion battery, offering up to 15 hours of runtime on a single charge.
- **High-Quality Illumination:** Features 160 LEDs rated at 90+ CRI for soft, even lighting that eliminates harsh shadows and blotchy colors.
- **Streamlined Design:** Seamlessly integrates with the iContact Camera Pro for a professional look with minimal clutter.
- **Portable and Reliable:** Perfect for extended sessions, ensuring consistent lighting in any environment.



Eye contact	The iContact Camera Pro and Light Panel accessory combine to elevate your virtual communication experience. The Light Panel enhances your appearance with adjustable color temperature, high-quality 90+ CRI LEDs for natural illumination, and a rechargeable battery for extended use. Seamlessly integrating with the iContact Camera Pro, it complements the camera's ability to enable natural eye contact—proven to boost trust, engagement, and performance. Together, they ensure you look professional and connect effectively, making virtual meetings more engaging and impactful.	
Superior LED	90+ CRI	A high 90+ CRI ensures accurate, natural color representation, making you look your best in any lighting environment.
	Adjustable	Adjustable brightness and color temperature color temperature from 2500-6500 to match any environment.
	Beam Angle	120° to brighten up you and your background.
	High Power	Up to 1150 LUX, nearly 10 times the power of the leading brand.
	Beam Angle	120°

Accessory mount	Our unique built-in accessory mount allows for seamless integration with the iContact Camera Pro.	
Compatibility	Works with Windows, MacOS, and most platforms and operating systems to ensure compatibility and seamless integration in the workplace.	
General	Dimensions and weight	Width: 115mm (5in) Height: 68mm (2.68in) Depth: 16mm (.63in) Weight: 129g (2.3oz) Cable length 1 m (4.9ft)
	What's in the box	Light panel with universal mount USB-C charging cable QuickStart guide
	Warranty	1-year limited hardware warranty
Battery	Long lasting 3100mAh lithium-ion battery for up to 15 hours of use between charges.	
Sustainability	Paper packaging: EPR-certified demonstrates compliance with environmental sustainability and recycling standards.	
Certifications	REACH, ROHS, FCC and CE certified	

iContact Camera

www.icontactcamera.com/Pro

Contact your reseller or contact us at www.icontactcamera.com/business

iContact Camera, Inc.
1309 Coffeen Ave
Suite 1200
Sheridan, WY 82801