



# KS-DR2104DBT

Marine / MotorSports Waterproof Compact 2/3/4 - Channel Class-D Amplifier with Bluetooth Controller



IPX7/IPX6 Waterproof



IP6X Dustproof



ASTM B117 Rustproof



Vibration-proof



### STRONG PROTECTION PERFORMANCE

- Waterproof & Dustproof IPX7/IPX6 Certified.
- Saltspray-proof ASTM B117 Corrosion Test Passed.
- Vibration-proof 3-Axis Multi-frequency Vibration Test Passed.
- Featuring Corrosion-Resistant Sealed Cast Aluminum Chassis with Silicon Seals, and Pigtail Cables with Molded Strain Relief Bushings.
- Stainless Steel Bottom Plate Assembly Screws.
- Efficient & Compact Class D Design - Allows to Install Anywhere in ATV/UTV, Watercraft, Motorcycle, Golf Cart, Classic Cars and etc...

### REMOTE CONTROL UNIT FEATURES

- Rugged Volume Knob Designed to be used Even While Wearing Gloves.
- Bluetooth® with 5 Device Connection.
- Qualcomm® aptX™ Technology for Improved Bluetooth Sound Quality.
- AAC Files are Supported for iPhone.
- Preset EQ: Choose by Pressing the EQ Key [1:Natural], [2:Rock], [3:Pops], [4:Easy], [5:Top40], [6:Jazz], [7:Powerful].
- Pre-Out/SW Level Control:  
Hold Down EQ key, then Control the Level by Rotating Knob.

### SPECIFICATIONS

- Efficient Class D Design
- 50 watts RMS x 4ch @ 4Ω
- 75 watts RMS x 4ch @ 2Ω
- 150 watts RMS x 2ch @ 4Ω
- 75 watts x 2 + 150 watts x 1 @ 4Ω
- Frequency Response: 10-20kHz (+0/-3dB)  
20-19kHz (+0/-1dB)
- Selectable, Variable HPF/LPF  
(50-200Hz, -12dB/octave)
- Channel Mode Control (2/3/4ch)
- Pre-Out (SW): 1 Pair (w/Level Control)
- Signal Sensing Turn-On
- In-Line Fuse with Rubber Cover (40A)
- 8.2' Wired Remote Control Cable.
- Amp Dimensions: 7-13/16 x 1-15/16 x 4-1/8

### REMOTE CONTROL INSTALLATION OPTIONS:

The remote can be surface mounted using the supplied double-sided tape, or flush-mounted in the included bracket. It also has a 1/4"-20 (Camera Style) thread that allows you to attach the remote to a generic bar mount kit. (not included)



UTV



ATV



MARINE



MOTORCYCLES



GOLF CARTS